


M9A393 Fiber - Loose Tube Armored - Flooded Core/Single Armor/Double Jacket


For more Information
please call

1-800-Belden1


Description:

FiberExpress Loose Tube (Campus) Armor Optical Fiber Cable Series is made up of rugged fiber cables for applications in hostile environments. This series of cables has corrugated steel armor which provides added protection for direct burial applications

Physical Characteristics (Overall)

Fiber Type:	50/125/250 Micron
Number of Fibers:	144
Core Diameter:	50 +/- 2.5
Core Non-Circularity:	5% Maximum
Clad Diameter:	125 +/- 2
Clad Non-Circularity:	1% Maximum
Primary Coating Material:	Acrylate
Primary Coating Diameter:	245 +/- 10
Secondary Coating Diameter:	250

Fiber Color Code Chart:

Color
Blue
Orange
Green
Brown
Slate
White
Red
Black
Yellow
Violet
Rose
Aqua

Buffer Tube Diameter:	1.9
Buffer Tube Material:	PBT - Polybutylene Terephthalate
Buffer Tube Filling Material:	Synthetic Thixotropic Gel

Buffer Tube Color Code Chart:

Number	Color
1	Blue
2	Orange
3	Green
4	Brown
5	Slate
6	White
7	Red
8	Black

M9A393 Fiber - Loose Tube Armored - Flooded Core/Single Armor/Double Jacket

9	Yellow
10	Violet
11	Rose
12	Aqua

Core-clad Offset: 1.5 Microns Maximum

Inner Jacket

Inner Jacket Nominal Wall Thickness: 0.03

Inner Jacket Ripcord: Yes

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
MDPE - Medium Density Polyethylene

Outer Jacket Nominal Wall Thickness: .060

Outer Jacket Diameter:

Nom. Dia. (in.)
0.870

Outer Jacket Ripcord: Aramid

Outer Jacket Color: Black

Strength Member

Strength Member Material: Fiberglass Epoxy Rod, Aramid Yarn

Armor

Armor Type: Corrugated

Armor Material: Steel

Armor Thickness: .006

Overall Cabling

Overall Cabling Fillers: Polyethylene

Overall Nominal Diameter: 0.870 in.

Mechanical Characteristics (Overall)

Storage Temperature Range: -50°C To +80°C

Operating Temperature Range: -40°C To +70°C

Min. Bend Radius (Install)/Minor Axis: 17.400 in.

Min. Bend Radius for Long Term Application: 13.050 in.

Crush Resistance: Passes TIA/EIA 455-41, 2000 N/cm

Impact Resistance: Passes TIA/EIA 455-25, 2000 Impacts w/1.6 N-m

Solar Radiation Resistance: High

Water Penetration: Passes TIA/EIA 455-82

Compound Flow: Passes TIA/EIA 455-81

Cyclic Flexing: Passes TIA/EIA 455-104

Twist Bend: Passes TIA/EIA 455-85

Max. Load for Installation: 600 lbs.

Max. Load for Long Term Application: 180 lbs.

Proof Test: 100 kpsi

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

M9A393 Fiber - Loose Tube Armored - Flooded Core/Single Armor/Double Jacket

IEEE Specification:	802.3Z
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2006
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Telecommunications Standards:	568B

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Burial:	Yes
Sunlight Resistance:	Yes

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Optical Characteristics (Overall)

Maximum Attenuation @ 850nm:	3.0 dB/km
Maximum Attenuation @ 1300nm:	1.0 dB/km
Point Loss @ 850nm & 1300nm:	.2
Minimum Bandwidth @ 850nm:	500 MHz*km
Minimum Bandwidth @ 1300nm:	500 MHz*km
Refractive Index @ 850nm:	1.496
Refractive Index @ 1300nm:	1.491
Numerical Aperture:	.2
Maximum Gigabit Ethernet Length @ 850nm:	600
Maximum Gigabit Ethernet Length @ 1300nm:	600

Notes (Overall)

Notes: Cable is flooded for moisture protection.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 0 Revision Date: 05-14-2007

© 2010 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide

M9A393 Fiber - Loose Tube Armored - Flooded Core/Single Armor/Double Jacket

for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.