


M9A500T Fiber - Loose Tube All Dielectric - Dry Core/Single PE Jacket



For more Information
please call

1-800-Belden1

**Description:**

FiberExpress Loose Tube Optical Fiber Cables are loose-tube buffered cables suited for outdoor applications such as lashed aerial or underground conduit.

Physical Characteristics (Overall)

Fiber Type:	50/125/250 Micron
Number of Fibers:	24
Core Diameter:	50 +/- 2.5
Core Non-Circularity:	5% Maximum
Clad Diameter:	125 +/- 2
Clad Non-Circularity:	2% Maximum
Primary Coating Material:	Acrylate
Primary Coating Diameter:	245 +/- 10
Secondary Coating Diameter:	250

Fiber Color Code Chart:

Color
Blue
Orange
Green
Brown
Slate
White

Buffer Tube Diameter:	1.9
Buffer Tube Material:	PBT - Polybutylene Terephthalate
Buffer Tube Filling Material:	Synthetic Thixotropic Gel

Buffer Tube Color Code Chart:

Number	Color
1	Blue
2	Orange
3	Green
4	Brown

Core-clad Offset:	3 Microns Maximum
--------------------------	-------------------

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material
MDPE - Medium Density Polyethylene

Outer Jacket Nominal Wall Thickness:	.055
Outer Jacket Ripcord:	Polyester
Outer Jacket Color:	Black

M9A500T Fiber - Loose Tube All Dielectric - Dry Core/Single PE Jacket**Strength Member**

Strength Member Material:	Fiberglass Epoxy Rod, Aramid Yarn
----------------------------------	-----------------------------------

Overall Cabling

Overall Cabling Fillers:	Polyethylene
Overall Nominal Diameter:	0.375 in.

Mechanical Characteristics (Overall)

Storage Temperature Range:	-50°C To +80°C
Operating Temperature Range:	-40°C To +70°C
Bulk Cable Weight:	46 lbs/1000 ft.
Min. Bend Radius (Install)/Minor Axis:	7.500 in.
Min. Bend Radius for Long Term Application:	5.600 in.
Crush Resistance:	Passes TIA/EIA 455-41, 2000 N/cm
Impact Resistance:	Passes TIA/EIA 455-25, 2000 Impacts w/1.6 N-m
Solar Radiation Resistance:	High
Water Penetration:	Passes TIA/EIA 455-82
Compound Flow:	Passes TIA/EIA 455-81
Cyclic Flexing:	Passes TIA/EIA 455-104
Max. Load for Installation:	600 lbs.
Max. Load for Long Term Application:	180 lbs.
Proof Test:	100 kpsi

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

IEEE Specification:	802.3Z
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2006
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Aerial:	Yes
Sunlight Resistance:	Yes

Plenum/Non-Plenum

Plenum (Y/N):	No
----------------------	----

Optical Characteristics (Overall)

Maximum Attenuation @ 850nm:	3.0 dB/km
Maximum Attenuation @ 1300nm:	1.0 dB/km
Point Loss @ 850nm & 1300nm:	0.2
Minimum Bandwidth @ 850nm:	500 MHz*km

M9A500T Fiber - Loose Tube All Dielectric - Dry Core/Single PE Jacket

Minimum Bandwidth @ 1300nm:	500 MHz*km
Refractive Index @ 850nm:	1.496
Refractive Index @ 1300nm:	1.491
Numerical Aperature:	0.200
Maximum Gigabit Ethernet Length @ 850nm:	600
Maximum Gigabit Ethernet Length @ 1300nm:	600

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 2 Revision Date: 05-14-2007

© 2010 Belden, Inc
 All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.