


M9A620 Fiber - Tight Buffer Distribution Cables - Plenum (OFNP)



For more Information
please call

1-800-Belden1

Description:

FiberExpress Optical Fiber Distribution Cables are designed for low to high fiber count in-building installations. They offer a high degree of flexibility for backbone and horizontal applications.

Physical Characteristics (Overall)

Fiber Type:	50/125/900 Micron
Number of Fibers:	72
Core Diameter:	50
Clad Diameter:	125
Primary Coating Material:	Acrylate
Primary Coating Diameter:	245
Secondary Coating Material:	Engineering Thermoplastic
Secondary Coating Diameter:	900

Fiber Color Code Chart:

Color
Blue
Orange
Green
Brown
Slate
White
Red
Black
Yellow
Violet
Rose
Aqua

Inner Jacket

Inner Jacket Nominal Wall Thickness:	0.020
---	-------

Inner Jacket Color Code Chart:

Number	Color
1	Blue
2	Orange
3	Green
4	Brown
5	Slate
6	White

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material
PVDF - Fluorocopolymer

Outer Jacket Nominal Wall Thickness:	0.030
---	-------

Outer Jacket Diameter:

Nom. Dia. (in.)
0.754

Outer Jacket Ripcord:	No
------------------------------	----

M9A620 Fiber - Tight Buffer Distribution Cables - Plenum (OFNP)

Outer Jacket Color:	Orange
Outer Jacket Separator Material:	Overall Polyester Tape, 25% overlap

Strength Member

Strength Member Material:	Aramid Yarn
---------------------------	-------------

Overall Cabling

Overall Nominal Diameter:	0.754 in.
---------------------------	-----------

Mechanical Characteristics (Overall)

Storage Temperature Range:	-40°C To +80°C
Operating Temperature Range:	-20°C To +70°C
Min. Bend Radius (Install)/Minor Axis:	11.310 in.
Min. Bend Radius for Long Term Application:	7.540 in.
Crush Resistance:	2000 N/cm
Impact Resistance:	2000 Impacts w/ 1.6 N-m
Cyclic Flexing:	2000 Cycles Min.
Max. Load for Installation:	2093 lbs.
Max. Load for Long Term Application:	523 lbs.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	OFNP
CEC/C(UL) Specification:	OFN
IEEE Specification:	802.3z
Telecommunications Standards:	568B

Flame Test

C(UL) Flame Test:	FT6
-------------------	-----

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	No

Plenum/Non-Plenum

Plenum (Y/N):	Yes
---------------	-----

Optical Characteristics (Overall)

Maximum Attenuation @ 850nm:	3.50 dB/km
Maximum Attenuation @ 1300nm:	1.25 dB/km
Minimum Bandwidth @ 850nm:	500 MHz*km
Minimum Bandwidth @ 1300nm:	500 MHz*km
Maximum Gigabit Ethernet Length @ 850nm:	600
Maximum Gigabit Ethernet Length @ 1300nm:	600

Notes (Overall)

Notes: This cable is designed for use in indoor applications. It can also be used in interbuilding applications as outlined in technical advisory #21.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

M9A620 Fiber - Tight Buffer Distribution Cables - Plenum (OFNP)

Revision Number: 0 Revision Date: 05-14-2007

© 2010 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.