


M9A701 Fiber - Micro Loose Tube



For more Information
please call

1-800-Belden1

Description:

Micro Loose Tube (Campus) Optical Fiber Cables are breakout style cables with the environmental advantages of a loose tube, gel filled cable. These cables are an ideal solution for indoor/outdoor installations.

Physical Characteristics (Overall)

Fiber Type:	50/125/900 Micron
Number of Fibers:	2
Core Diameter:	50
Clad Diameter:	125
Primary Coating Material:	Acrylate
Primary Coating Diameter:	245
Secondary Coating Material:	Engineering Thermoplastic
Secondary Coating Diameter:	900
Buffer Tube Material:	PBT - Polybutylene Terephthalate
Buffer Tube Filling Material:	Synthetic Thixotropic Gel

Inner Jacket

Inner Jacket Color Code Chart:

Number	Color
1	Blue
2	Orange

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PE - Polyethylene

Outer Jacket Nominal Wall Thickness: 0.060

Outer Jacket Diameter:

Nom. Dia. (in.)
0.360

Outer Jacket Ripcord: No

Outer Jacket Color: Black

Outer Jacket Separator Material: Overall Polyeste Tape, 25% overlap

Strength Member

Strength Member Material: Aramid Yarn

Overall Cabling

Overall Nominal Diameter: 0.360 in.

Mechanical Characteristics (Overall)

Storage Temperature Range:	-40°C To +70°C
Operating Temperature Range:	-20°C To +70°C
Min. Bend Radius (Install)/Minor Axis:	7.200 in.
Min. Bend Radius for Long Term Application:	5.400 in.

M9A701 Fiber - Micro Loose Tube

Crush Resistance:	600 N/cm
Impact Resistance:	20 Impacts w/ 1.0 N-m
Max. Load for Installation:	345 lbs.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

IEEE Specification:	802.3z
Telecommunications Standards:	568B

Plenum/Non-Plenum

Plenum (Y/N):	No
----------------------	----

Optical Characteristics (Overall)

Maximum Attenuation @ 850nm:	3.50 dB/km
Maximum Attenuation @ 1300nm:	1.25 dB/km
Minimum Bandwidth @ 850nm:	500 MHz*km
Minimum Bandwidth @ 1300nm:	500 MHz*km
Maximum Gigabit Ethernet Length @ 850nm:	600
Maximum Gigabit Ethernet Length @ 1300nm:	600

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 0 Revision Date: 04-14-2008

© 2010 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.