


## M9A841 Fiber - Loose Tube All Dielectric - Dry Core/Double PE Jacket



For more Information  
please call

1-800-Belden1

**Description:**

Loose Tube All Dielectric - Dry Core/Double PE Jacket.

**Physical Characteristics (Overall)**

Fiber Type:	50/125/250 Micron
Number of Fibers:	4
Core Diameter:	50 +/- 2.5
Core Non-Circularity:	5% Maximum
Clad Diameter:	125 +/- 2
Clad Non-Circularity:	2% Maximum
Primary Coating Material:	Acrylate
Primary Coating Diameter:	245 +/- 10
Secondary Coating Diameter:	250

**Fiber Color Code Chart:**

Color
Blue
Orange
Green
Brown

Buffer Tube Diameter:	1.9
Buffer Tube Material:	PBT - Polybutylene Terephthalate
Buffer Tube Filling Material:	Synthetic Thixotropic Gel

**Buffer Tube Color Code Chart:**

Number	Color
1	Blue

Core-clad Offset:	3 Microns Maximum
-------------------	-------------------

**Inner Jacket**

Inner Jacket Ripcord:	Yes
-----------------------	-----

**Outer Jacket****Outer Jacket Material:**

Outer Jacket Material
MDPE - Medium Density Polyethylene

Outer Jacket Ripcord:	Polyester
Outer Jacket Color:	Black

**Strength Member**

Strength Member Material:	Fiberglass Epoxy Rod, Aramid Yarn
---------------------------	-----------------------------------

**Overall Cabling**

Overall Cabling Fillers:	Polyethylene
Overall Nominal Diameter:	0.440 in.

**Mechanical Characteristics (Overall)**

Storage Temperature Range:	-50°C To +80°C
----------------------------	----------------

**M9A841 Fiber - Loose Tube All Dielectric - Dry Core/Double PE Jacket**

Operating Temperature Range:	-40°C To +70°C
Bulk Cable Weight:	60 lbs/1000 ft.
Min. Bend Radius (Install)/Minor Axis:	8.800 in.
Min. Bend Radius for Long Term Application:	6.600 in.
Crush Resistance:	Passes TIA/EIA 455-41; 2000 N/cm
Impact Resistance:	Passes TIA/EIA 455-25; 2000 Impacts @ 1.6 N-m
Solar Radiation Resistance:	High
Water Penetration:	Passes TIA/EIA 455-82
Compound Flow:	Passes TIA/EIA 455-81
Cyclic Flexing:	Passes TIA/EIA 455-104
Max. Load for Installation:	600 lbs.
Max. Load for Long Term Application:	180 lbs.
Proof Test:	100 kpsi

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

IEEE Specification:	802.3Z
---------------------	--------

**Suitability**

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Aerial:	Yes
Suitability - Burial:	Yes
Sunlight Resistance:	Yes

**Plenum/Non-Plenum**

Plenum (Y/N):	No
---------------	----

**Optical Characteristics (Overall)**

Maximum Attenuation @ 850nm:	3.0 dB/km
Maximum Attenuation @ 1300nm:	1.0 dB/km
Point Loss @ 850nm & 1300nm:	0.2
Minimum Bandwidth @ 850nm:	500 MHz*km
Minimum Bandwidth @ 1300nm:	500 MHz*km
Refractive Index @ 850nm:	1.496
Refractive Index @ 1300nm:	1.491
Numerical Aperture:	.200
Maximum Gigabit Ethernet Length @ 850nm:	600
Maximum Gigabit Ethernet Length @ 1300nm:	600

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 3    Revision Date: 05-14-2007

© 2010 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications

---

**M9A841 Fiber - Loose Tube All Dielectric - Dry Core/Double PE Jacket**

described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.