

M9B018 Fiber - Tight Buffer Breakout Cables (2.0 mm subunits)-Plenum (OFNP)


For more Information
please call

1-800-Belden1


Description:

FiberExpress Optical Fiber Breakout Cables are designed for low to medium fiber count in-building, harsh-environment installations. Breakout or fanout cables offer a high degree of flexibility for backbone and horizontal applications.

Physical Characteristics (Overall)

Fiber Type:	62.5/125/900 Micron
Number of Fibers:	12
Core Diameter:	62.5
Clad Diameter:	125
Primary Coating Material:	Acrylate
Primary Coating Diameter:	245
Secondary Coating Material:	Plenum Grade PVC - Polyvinyl Chloride
Secondary Coating Diameter:	900

Fiber Color Code Chart:

Color
Slate

Inner Jacket

Inner Jacket Nominal Wall Thickness:	0.078
---	-------

Inner Jacket Color Code Chart:

Number	Color
1	Blue
2	Orange
3	Green
4	Brown
5	Slate
6	White
7	Red
8	Black
9	Yellow
10	Violet
11	Rose
12	Aqua

Outer Jacket
Outer Jacket Material:

Outer Jacket Material
Plenum Grade PVC - Polyvinyl Chloride

Outer Jacket Nominal Wall Thickness:	0.030
---	-------

Outer Jacket Diameter:

Nom. Dia. (in.)
0.391

M9B018 Fiber - Tight Buffer Breakout Cables (2.0 mm subunits)-Plenum (OFNP)

Outer Jacket Color:	Orange
---------------------	--------

Strength Member

Strength Member Material:	Aramid Yarn, Fiberglass Epoxy Rod
---------------------------	-----------------------------------

Overall Cabling

Overall Nominal Diameter:	0.391 in.
---------------------------	-----------

Mechanical Characteristics (Overall)

Storage Temperature Range:	-40°C To +80°C
Operating Temperature Range:	-20°C To +70°C
Min. Bend Radius (Install)/Minor Axis:	5.865 in.
Min. Bend Radius for Long Term Application:	3.910 in.
Crush Resistance:	2000 N/cm
Impact Resistance:	2000 Impacts w/ 1.6 N-m
Cyclic Flexing:	2000 Cycles min.
Max. Load for Installation:	600 lbs.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	OFNP
CEC/C(UL) Specification:	OFN
IEEE Specification:	802.3z
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2006
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Telecommunications Standards:	568B

Flame Test

C(UL) Flame Test:	FT6
-------------------	-----

Plenum/Non-Plenum

Plenum (Y/N):	Yes
---------------	-----

Optical Characteristics (Overall)

Maximum Attenuation @ 850nm:	3.50 dB/km
Maximum Attenuation @ 1300nm:	1.25 dB/km
Minimum Bandwidth @ 850nm:	200 MHz*km
Minimum Bandwidth @ 1300nm:	500 MHz*km
Maximum Gigabit Ethernet Length @ 850nm:	300
Maximum Gigabit Ethernet Length @ 1300nm:	550

Notes (Overall)

Notes: This cable is verified for use in indoor horizontal/backbone applications. It can also be used in interbuilding applications as outlined in Mohawk/CDT technical advisory # 21.

Put Ups and Colors:

M9B018 Fiber - Tight Buffer Breakout Cables (2.0 mm subunits)-Plenum (OFNP)

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 0 Revision Date: 05-14-2007

© 2010 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.