

## M9B034 Fiber - Tight Buffer Breakout Cables (2.5 mm subunits)-Plenum (OFNP)



For more Information  
please call

1-800-Belden1

**Description:**

FiberExpress Optical Fiber Breakout Cables are designed for low to medium fiber count in-building, harsh-environment installations. Breakout or fanout cables offer a high degree of flexibility for backbone and horizontal applications.

**Physical Characteristics (Overall)**

<b>Fiber Type:</b>	62.5/125/900 Micron
<b>Number of Fibers:</b>	12
<b>Core Diameter:</b>	62.5 +/- 2.5
<b>Core Non-Circularity:</b>	5% Maximum
<b>Clad Diameter:</b>	125 +/- 2
<b>Clad Non-Circularity:</b>	1% Maximum
<b>Primary Coating Material:</b>	Acrylate
<b>Primary Coating Diameter:</b>	245 +/- 10
<b>Secondary Coating Material:</b>	Plenum Grade PVC - Polyvinyl Chloride
<b>Secondary Coating Diameter:</b>	900 +/- 50
<b>Breakout Element Diameter:</b>	.098
<b>Breakout Element Material:</b>	Plenum Grade PVC - Polyvinyl Chloride

**Buffer Tube Color Code Chart:**

Number	Color
1	Blue
2	Orange
3	Green
4	Brown
5	Slate
6	White
7	Red
8	Black
9	Yellow
10	Violet
11	Rose
12	Aqua

<b>Core-clad Offset:</b>	1.5 Microns Maximum
--------------------------	---------------------

**Outer Jacket****Outer Jacket Material:**

Outer Jacket Material
Plenum Grade PVC - Polyvinyl Chloride

<b>Outer Jacket Color:</b>	Orange
----------------------------	--------

**Strength Member**

<b>Strength Member Material:</b>	Aramid Yarn
----------------------------------	-------------

**Overall Cabling**

<b>Overall Nominal Diameter:</b>	0.475 in.
----------------------------------	-----------

**Mechanical Characteristics (Overall)**

<b>Storage Temperature Range:</b>	-40°C To +80°C
-----------------------------------	----------------

**M9B034 Fiber - Tight Buffer Breakout Cables (2.5 mm subunits)-Plenum (OFNP)**

Operating Temperature Range:	-20°C To +70°C
Bulk Cable Weight:	140 lbs/1000 ft.
Min. Bend Radius (Install)/Minor Axis:	7.200 in.
Min. Bend Radius for Long Term Application:	4.800 in.
Crush Resistance:	EIA-455-41, 2000 N/cm
Impact Resistance:	EIA-455-25, 2000 Impacts w/1.6 N-m
Cyclic Flexing:	EIA-455-104 2000 Cycles min.
Max. Load for Installation:	600 lbs.
Max. Load for Long Term Application:	150 lbs.
Proof Test:	100 kpsi

**Applicable Specifications and Agency Compliance (Overall)**
**Applicable Standards & Environmental Programs**

IEEE Specification:	802.3Z
---------------------	--------

**Flame Test**

UL Flame Test:	OFNP, NFPA 262
C(UL) Flame Test:	OFNP
CSA Flame Test:	FT6

**Suitability**

Suitability - Indoor:	Yes
Suitability - Outdoor:	No
Sunlight Resistance:	No

**Plenum/Non-Plenum**

Plenum (Y/N):	Yes
---------------	-----

**Optical Characteristics (Overall)**

Maximum Attenuation @ 850nm:	3.5 dB/km
Maximum Attenuation @ 1300nm:	1.25 dB/km
Point Loss @ 850nm & 1300nm:	.2
Minimum Bandwidth @ 850nm:	200 MHz*km
Minimum Bandwidth @ 1300nm:	500 MHz*km
Refractive Index @ 850nm:	1.496
Refractive Index @ 1300nm:	1.491
Numerical Aperature:	.275
Maximum Gigabit Ethernet Length @ 850nm:	300
Maximum Gigabit Ethernet Length @ 1300nm:	550

**Notes (Overall)**

**Notes:** Note: Outdoor installation must be in conduit or protected from UV exposure.

**Reference (Overall)**

Previous Part Number:	MTBP612
-----------------------	---------

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

---

**M9B034 Fiber - Tight Buffer Breakout Cables (2.5 mm subunits)-Plenum (OFNP)**

---

Revision Number: 4    Revision Date: 05-14-2007

© 2010 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.