

M9B847 Fiber - Loose Tube All Dielectric - Dry Core/Double PE Jacket



For more Information
please call

1-800-Belden1

Description:

Loose Tube All Dielectric - Dry Core/Double PE Jacket.

Physical Characteristics (Overall)

Fiber Type:	62.5/125/245 Micron
Number of Fibers:	36
Core Diameter:	62.5 +/- 2.5
Core Non-Circularity:	5% Maximum
Clad Diameter:	125 +/- 2
Clad Non-Circularity:	1% Maximum
Primary Coating Material:	Acrylate
Primary Coating Diameter:	245 +/- 10

Fiber Color Code Chart:

Color
Blue
Orange
Green
Brown
Slate
White

Buffer Tube Diameter:	1.9
Buffer Tube Material:	PBT - Polybutylene Terephthalate
Buffer Tube Filling Material:	Synthetic Thixotropic Gel

Buffer Tube Color Code Chart:

Number	Color
1	Blue
2	Orange
3	Green
4	Brown
5	Slate
6	White

Core-clad Offset:	1.5 Microns Maximum
--------------------------	---------------------

Inner Jacket

Inner Jacket Ripcord:	Yes
------------------------------	-----

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material
MDPE - Medium Density Polyethylene

Outer Jacket Ripcord:	Polyester
Outer Jacket Color:	Black

Strength Member

Strength Member Material:	Fiberglass Epoxy Rod, Aramid Yarn
----------------------------------	-----------------------------------

Overall Cabling

Overall Nominal Diameter:	0.440 in.
----------------------------------	-----------

M9B847 Fiber - Loose Tube All Dielectric - Dry Core/Double PE Jacket**Mechanical Characteristics (Overall)**

Storage Temperature Range:	-50°C To +80°C
Operating Temperature Range:	-40°C To +70°C
Bulk Cable Weight:	60 lbs/1000 ft.
Min. Bend Radius (Install)/Minor Axis:	8.800 in.
Min. Bend Radius for Long Term Application:	6.600 in.
Crush Resistance:	Passes TIA/EIA 455-41, 2000 N/cm
Impact Resistance:	Passes TIA/EIA 455-25, 2000 Impacts w/1.6 N-m
Solar Radiation Resistance:	High
Water Penetration:	Passes TIA/EIA 455-82
Compound Flow:	Passes TIA/EIA 455-81
Max. Load for Installation:	600 lbs.
Max. Load for Long Term Application:	180 lbs.
Proof Test:	100 kpsi

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

IEEE Specification:	802.3Z
---------------------	--------

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Aerial:	Yes
Suitability - Burial:	Yes
Sunlight Resistance:	No

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Optical Characteristics (Overall)

Maximum Attenuation @ 850nm:	3.25 dB/km
Maximum Attenuation @ 1300nm:	1.0 dB/km
Point Loss @ 850nm & 1300nm:	0.2
Minimum Bandwidth @ 850nm:	200 MHz*km
Minimum Bandwidth @ 1300nm:	500 MHz*km
Refractive Index @ 850nm:	1.496
Refractive Index @ 1300nm:	1.491
Numerical Aperture:	0.275
Maximum Gigabit Ethernet Length @ 850nm:	300
Maximum Gigabit Ethernet Length @ 1300nm:	550

Reference (Overall)

Previous Part Number:	MLD6036
-----------------------	---------

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

M9B847 Fiber - Loose Tube All Dielectric - Dry Core/Double PE Jacket

Revision Number: 3 Revision Date: 05-14-2007

© 2010 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.