


M9D001 Fiber - Tight Buffer Interconnect Cables - Riser (OFNR)



OUTER JACKET
 ARAMID STRENGTH
 ELEMENTS
 TIGHT BUFFERED
 FIBER



For more Information
 please call

1-800-Belden1

Description:

Interconnect Cables are designed for low fiber-count premises environments. They are small and very flexible, making them ideal for confined spaces. Their aesthetic appearance makes these cables suitable for use in open office environments.

Physical Characteristics (Overall)

Fiber Type:	62.5/125/900 Micron
Number of Fibers:	1
Core Diameter:	62.5
Clad Diameter:	125
Primary Coating Material:	Acrylate
Primary Coating Diameter:	245
Secondary Coating Material:	Engineering Thermoplastic
Secondary Coating Diameter:	900

Fiber Color Code Chart:

Color
Slate

Outer Jacket**Outer Jacket Material:****Outer Jacket Material**

PVC - Polyvinyl Chloride

Outer Jacket Nominal Wall Thickness: 0.025

Outer Jacket Diameter:**Nom. Dia. (in.)**

0.114

Outer Jacket Color: Slate

Strength Member

Strength Member Material: Aramid Yarn

Overall Cabling

Overall Nominal Diameter: 0.114 in.

Mechanical Characteristics (Overall)

Storage Temperature Range:	-40°C To +70°C
Operating Temperature Range:	-20°C To +70°C
Bulk Cable Weight:	6 lbs/1000 ft.
Min. Bend Radius (Install)/Minor Axis:	1.500 in.
Min. Bend Radius for Long Term Application:	1.100 in.
Crush Resistance:	200 N/cm
Impact Resistance:	20 Impacts w/ 1.0 N-m
Cyclic Flexing:	100 Cycles min.
Max. Load for Installation:	90 lbs.

M9D001 Fiber - Tight Buffer Interconnect Cables - Riser (OFNR)

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	OFNR
CEC/C(UL) Specification:	OFN
IEEE Specification:	802.3z
Telecommunications Standards:	568B

Flame Test

C(UL) Flame Test:	FT4
-------------------	-----

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Optical Characteristics (Overall)

Maximum Attenuation @ 850nm:	3.50 dB/km
Maximum Attenuation @ 1300nm:	1.25 dB/km
Minimum Bandwidth @ 850nm:	200 MHz*km
Minimum Bandwidth @ 1300nm:	500 MHz*km
Maximum Gigabit Ethernet Length @ 850nm:	500
Maximum Gigabit Ethernet Length @ 1300nm:	1000

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 0 Revision Date: 05-14-2007

© 2010 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.