


M9W013 Fiber - Tight Buffer Breakout Cables (2.0 mm subunits)-Plenum (OFNP)



OUTER JACKET
SUB-UNIT JACKET
ARAMID STRENGTH
ELEMENTS
STRENGTH MEMBERS
TIGHT BUFFERED
FIBER



For more Information
please call

1-800-Belden1

Description:

FiberExpress Optical Fiber Breakout Cables are designed for low to medium fiber count in-building, harsh-environment installations. Breakout or fanout cables offer a high degree of flexibility for backbone and horizontal applications.

Physical Characteristics (Overall)

Fiber Type:	Single Mode/125/900 Micron
Number of Fibers:	2
Core Diameter:	8.3
Clad Diameter:	125
Primary Coating Material:	Acrylate
Primary Coating Diameter:	245
Secondary Coating Material:	Engineering Thermoplastic
Secondary Coating Diameter:	900

Fiber Color Code Chart:

Color
Slate

Inner Jacket**Inner Jacket Color Code Chart:**

Number	Color
1	Blue
2	Orange

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material
Plenum Grade PVC - Polyvinyl Chloride

Outer Jacket Nominal Wall Thickness: 0.030

Outer Jacket Diameter:

Nom. Dia. (in.)
0.230

Outer Jacket Color: Yellow

Strength Member

Strength Member Material: Aramid Yarn, Fiberglass Epoxy Rod

Overall Cabling

Overall Nominal Diameter: 0.230 in.

Mechanical Characteristics (Overall)

Storage Temperature Range:	-40°C To +80°C
Operating Temperature Range:	-20°C To +70°C
Min. Bend Radius (Install)/Minor Axis:	3.450 in.
Min. Bend Radius for Long Term Application:	2.300 in.
Crush Resistance:	2000 N/cm
Impact Resistance:	2000 Impacts w/1.6 N•m

M9W013 Fiber - Tight Buffer Breakout Cables (2.0 mm subunits)-Plenum (OFNP)

Cyclic Flexing:	2000 Cycles min.
Max. Load for Installation:	180 lbs.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	OFNP
CEC/C(UL) Specification:	OFN
Telecommunications Standards:	568B
Other Specification:	ITU G.652.d

Flame Test

C(UL) Flame Test:	FT6
--------------------------	-----

Plenum/Non-Plenum

Plenum (Y/N):	Yes
----------------------	-----

Optical Characteristics (Overall)

Maximum Attenuation @ 1310nm:	0.80 dB/km
Maximum Attenuation @ 1550nm:	0.50 dB/km

Notes (Overall)

Notes: This cable is designed for use in indoor applications. It can also be used in interbuilding applications as outlined in technical advisory # 21.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 0 Revision Date: 05-14-2007

© 2010 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.