

M9W240 Fiber - Tight Buffer Aluminum Interlock Armor Cables - Plenum (OFCP)



For more Information
please call

1-800-Belden1

Description:

FiberExpress Interlock Armor Optical Fiber cables have a rugged construction that affords superior protection in adverse environments yet can also be installed in general purpose, riser and plenum environments.

Physical Characteristics (Overall)

Fiber Type:	Single Mode/125/900 Micron
Number of Fibers:	6
Core Diameter:	8.3
Clad Diameter:	125
Primary Coating Material:	245
Secondary Coating Material:	Plenum Grade PVC - Polyvinyl Chloride
Secondary Coating Diameter:	900

Fiber Color Code Chart:

Color
Blue
Orange
Green
Brown
Slate
White

Core-clad Offset:	Acrylate
--------------------------	----------

Inner Jacket

Inner Jacket Nominal Wall Thickness:	0.025
---	-------

Inner Jacket Color Code Chart:

Number	Color
1	Yellow

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material
Plenum Grade PVC - Polyvinyl Chloride

Outer Jacket Nominal Wall Thickness:	0.028
---	-------

Outer Jacket Diameter:

Nom. Dia. (in.)
0.471

Outer Jacket Color:	Yellow
----------------------------	--------

Strength Member

Strength Member Material:	Aramid Yarn
----------------------------------	-------------

Aramid

Aramid Type:	Interlocking
Aramid Material:	Aluminum
Diameter over Aramid:	0.415

Overall Cabling

Overall Nominal Diameter:	0.471 in.
----------------------------------	-----------

M9W240 Fiber - Tight Buffer Aluminum Interlock Armor Cables - Plenum (OFCP)

Mechanical Characteristics (Overall)

Storage Temperature Range:	-40°C To +80°C
Operating Temperature Range:	-20°C To +70°C
Min. Bend Radius (Install)/Minor Axis:	9.420 in.
Min. Bend Radius for Long Term Application:	7.065 in.
Crush Resistance:	2000 N/cm
Impact Resistance:	2000 Impacts w/ 1.6 N-m
Cyclic Flexing:	2000 Cycles min.
Max. Load for Installation:	270 lbs.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	OFCP
CEC/C(UL) Specification:	OFC
Telecommunications Standards:	568B
Other Specification:	ITU G.652.d

Flame Test

C(UL) Flame Test:	FT6
-------------------	-----

Plenum/Non-Plenum

Plenum (Y/N):	Yes
---------------	-----

Optical Characteristics (Overall)

Maximum Attenuation @ 1310nm:	0.80 dB/km
Maximum Attenuation @ 1550nm:	0.50 dB/km

Notes (Overall)

Notes: This cable is designed for use in indoor applications. It can also be used in interbuilding applications as outlined as technical advisory #21.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 0 Revision Date: 05-14-2007

© 2010 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.