


M9W619 Fiber - Tight Buffer Distribution Cables - Riser (OFNR)



For more Information
please call

1-800-Belden1

Description:

FiberExpress Optical Fiber Distribution Cables are designed for low to high fiber count in-building installations. They offer a high degree of flexibility for backbone and horizontal applications.

Physical Characteristics (Overall)

Fiber Type:	Single Mode/125/900 Micron
Number of Fibers:	144
Core Diameter:	8.3
Mode Field Diameter @ 1310nm:	9.2 +/- 0.4
Mode Field Diameter @1550nm:	10.5 +/- 1.0
Clad Diameter:	125 +/- 1
Clad Non-Circularity:	1% Maximum
Core-clad Concentricity Error:	0.6 Microns Maximum
Primary Coating Material:	Acrylate
Primary Coating Diameter:	245 +/- 10
Secondary Coating Material:	Engineering Thermoplastic
Secondary Coating Diameter:	900 +/- 50

Fiber Color Code Chart:

Color
Blue
Orange
Green
Brown
Slate
White
Red
Black
Yellow
Violet
Rose
Aqua

Core-clad Offset:	0.6 Microns Maximum
--------------------------	---------------------

Inner Jacket

Inner Jacket Nominal Wall Thickness:	0.025
---	-------

Inner Jacket Color Code Chart:

Number	Color
1	Blue
2	Orange
3	Green
4	Brown
5	Slate
6	White
7	Red
8	Black
9	Yellow
10	Violet
11	Rose

M9W619 Fiber - Tight Buffer Distribution Cables - Riser (OFNR)

12	Aqua
----	------

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Nominal Wall Thickness: 0.057

Outer Jacket Diameter:

Nom. Dia. (in.)
0.964

Outer Jacket Color: Yellow

Outer Jacket Separator Material: Overall Polyester Tape, 25% Overlap

Strength Member

Strength Member Material: Aramid Yarn, Fiberglass Epoxy Rod

Overall Cabling

Overall Nominal Diameter: 0.964 in.

Mechanical Characteristics (Overall)

Storage Temperature Range: -40°C To +80°C

Operating Temperature Range: -20°C To +70°C

Min. Bend Radius (Install)/Minor Axis: 14.460 in.

Min. Bend Radius for Long Term Application: 9.640 in.

Crush Resistance: 2000 N/cm

Impact Resistance: 2000 Impacts w/ 1.6 N-m

Cyclic Flexing: 2000 Cycles min.

Max. Load for Installation: 2745 lbs.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: OFNR

CEC/C(UL) Specification: OFN

Telecommunications Standards: 568B

Other Specification: ITU G.652.d

Flame Test

C(UL) Flame Test: FT4

Suitability

Suitability - Indoor: Yes

Suitability - Outdoor: No

Plenum/Non-Plenum

Plenum (Y/N): No

Optical Characteristics (Overall)

Maximum Attenuation @ 1310nm: 0.8 dB/km

Maximum Attenuation @ 1550nm: 0.5 dB/km

Notes (Overall)

Notes: This cable is designed for use in indoor applications. It can also be used in interbuilding applications as outlined as technical advisory #21.

M9W619 Fiber - Tight Buffer Distribution Cables - Riser (OFNR)**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 0 Revision Date: 05-14-2007

© 2010 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.