

## M9W811 Fiber - Loose Tube Indoor/Outdoor All Dielectric Dry Core-Riser OFNR



For more Information  
please call

1-800-Belden1



### Description:

FiberExpress Loose Tube Optical Fiber Cables are loose-tube buffered cables suited for outdoor applications such as lashed aerial or underground conduit.

### Physical Characteristics (Overall)

Fiber Type:	Single Mode 125/245 Micron
Number of Fibers:	12
Core Diameter:	8.3
Clad Diameter:	125
Primary Coating Material:	Acrylate
Primary Coating Diameter:	245
Secondary Coating Material:	Engineering Thermoplastic
Secondary Coating Diameter:	250

#### Fiber Color Code Chart:

Color
Blue
Orange
Green
Brown
Slate
White

Buffer Tube Diameter:	1.9
Buffer Tube Material:	PBT - Polybutylene Terephthalate
Buffer Tube Filling Material:	Synthetic Thixotropic Gel

#### Buffer Tube Color Code Chart:

Number	Color
1	Blue
2	Orange

### Outer Jacket

#### Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Nominal Wall Thickness:	0.060
--------------------------------------	-------

#### Outer Jacket Diameter:

Nom. Dia. (in.)
0.380

Outer Jacket Ripcord:	Yes
Outer Jacket Color:	Black

### Strength Member

Strength Member Material:	Aramid Yarn, Fiberglass Epoxy Rod
---------------------------	-----------------------------------

**M9W811 Fiber - Loose Tube Indoor/Outdoor All Dielectric Dry Core-Riser OFNR****Overall Cabling**

Overall Nominal Diameter:	0.380 in.
---------------------------	-----------

**Mechanical Characteristics (Overall)**

Storage Temperature Range:	-40°C To +80°C
Operating Temperature Range:	-40°C To +70°C
Min. Bend Radius (Install)/Minor Axis:	7.600 in.
Min. Bend Radius for Long Term Application:	5.700 in.
Crush Resistance:	2000 N/cm
Impact Resistance:	2000 Impacts w/ 1.6 N-m
Max. Load for Installation:	600 lbs.
Max. Load for Long Term Application:	150 lbs.

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	OFNR
CEC/C(UL) Specification:	OFN
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2006
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Telecommunications Standards:	568B
Other Specification:	ITU G.652.d

**Flame Test**

C(UL) Flame Test:	FT4
-------------------	-----

**Plenum/Non-Plenum**

Plenum (Y/N):	No
---------------	----

**Optical Characteristics (Overall)**

Maximum Attenuation @ 1310nm:	0.40 dB/km
Maximum Attenuation @ 1550nm:	0.30 dB/km

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 0    Revision Date: 05-14-2007

© 2010 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

---

## M9W811 Fiber - Loose Tube Indoor/Outdoor All Dielectric Dry Core-Riser OFNR

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.