

M9W817 Fiber - Loose Tube Indoor/Outdoor All Dielectric Dry Core-Riser OFNR

For more Information
please call

1-800-Belden1

Description:

FiberExpress Loose Tube Optical Fiber Cables are loose-tube buffered cables suited for outdoor applications such as lashed aerial or underground conduit.

Physical Characteristics (Overall)

Fiber Type:	Single Mode 125/245 Micron
Number of Fibers:	144
Core Diameter:	8.3
Clad Diameter:	125
Primary Coating Material:	Acrylate
Primary Coating Diameter:	245
Secondary Coating Material:	Engineering Thermoplastic
Secondary Coating Diameter:	250

Fiber Color Code Chart:

Color
Blue
Orange
Green
Brown
Slate
White
Red
Black
Yellow
Violet
Rose
Aqua

Buffer Tube Diameter:	2.8
Buffer Tube Material:	Flame Retardant Thermoplastic
Buffer Tube Filling Material:	Synthetic Thixotropic Gel

Buffer Tube Color Code Chart:

Number	Color
1	Blue
2	Orange
3	Green
4	Brown
5	Slate
6	White
7	Red
8	Black
9	Yellow
10	Violet
11	Rose
12	Aqua

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

M9W817 Fiber - Loose Tube Indoor/Outdoor All Dielectric Dry Core-Riser OFNR

Outer Jacket Nominal Wall Thickness: 0.060

Outer Jacket Diameter:

Nom. Dia. (in.)

0.700

Outer Jacket Ripcord: Yes

Outer Jacket Color: Black

Outer Jacket Separator Material: Overall Water Blocking Tape, 25% overlap

Strength Member

Strength Member Material: Aramid Yarn, Fiberglass Epoxy Rod

Overall Cabling

Overall Nominal Diameter: 0.700 in.

Mechanical Characteristics (Overall)

Storage Temperature Range: -40°C To +80°C

Operating Temperature Range: -40°C To +70°C

Min. Bend Radius (Install)/Minor Axis: 14 in.

Min. Bend Radius for Long Term Application: 10.500 in.

Crush Resistance: 2000 N/cm

Impact Resistance: 2000 Impacts w/ 1.6 N-m

Max. Load for Installation: 600 lbs.

Max. Load for Long Term Application: 150 lbs.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

NEC/(UL) Specification: OFNR

CEC/C(UL) Specification: OFN

Telecommunications Standards: 568B

Other Specification: ITU G.652.d

Flame Test

C(UL) Flame Test: FT4

Plenum/Non-Plenum

Plenum (Y/N): No

Optical Characteristics (Overall)

Maximum Attenuation @ 1310nm: 0.40 dB/km

Maximum Attenuation @ 1550nm: 0.30 dB/km

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 0 Revision Date: 05-14-2007

© 2010 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

M9W817 Fiber - Loose Tube Indoor/Outdoor All Dielectric Dry Core-Riser OFNR

All sales of Belden products are subject to Belden's standard terms and conditions of sale.