

## SNS1PFFK Drop Connectors - Cable to "F" Female Precision Connector Environmentally Sealed



For more Information  
please call

1-800-Belden1

**Description:**

Cable to "F" Female Precision Connector Environmentally Sealed, Compression F Female

**Usage (Overall)**

Suitable Applications: Broadband, CATV

**Physical Characteristics (Connectivity)****Product Family:**

Part Number	Cable Type	Description	Post I.D. (in.)	Inner Pack	Sleeve I.D. (in.)	Sleeve Color	Outer Pack	Master Pack	Tool
SNS1P59FFK	RG-59		0.154	10	0.275	Orange	50	500	SNSUTL, CST596711, CST596
SNS1P59QSFFK	RG-59 Quad Shield		0.154	10	0.275	Green	50	500	SNSUTL, CST596711, CST596
SNS1P6FFK	RG-6		0.191	10	0.290	Blue	50	500	SNSUTL, CST596711, CST596
SNS1P6QSFFK	RG-6 Quad Shield		0.191	10	0.315	Violet	50	500	SNSUTL, CST596711, CST596
SNS1P6UFFK	RG-6	Ultimate	0.191	10	0.293	Red	50	500	SNSUTL, CST596711, CST596

**Connector Type:** F Female Precision

**Body:** NiTin Plated Brass

**Post:** Tin-Plated Brass

**Terminal/Contact:** Tin-Plated Copper Alloy

**Insulators:** Polypropylene

**O-Rings:** Ethylene Propylene

**Mechanical Characteristics (Connectivity)**

**Cable Insertion Force (Max./lbs.):** 20

**Cable Retention Force:** 40 lbs. min. per ANSI/SCTE 99 2004

**Temperature Rating:** -40°C To +60°C, -40°F To +140°F

**Salt Fog:** Passes 1000 hours ASTM B 117

**Moisture Migration:** Passes ANSI/SCTE 60 2004

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

**EU Directive 2002/95/EC (RoHS):** Yes

**EU RoHS Compliance Date (mm/dd/yyyy):** 11/25/2008

**Electrical Characteristics (Overall)**

**Return Loss (typical):** >=-30 dB up to 1 GHz

**Insertion Loss:** <=-0.20 dB up to 1 GHz

**RFI Shielding (typical):** -85 dB (60 percent Bonded Foil)

## SNS1PFFK Drop Connectors - Cable to "F" Female Precision Connector Environmentally Sealed

### Related Documents:

No related documents are available for this product

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 0    Revision Date: 08-26-2011

© 2012 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.