

SNS1PRCA Drop Connectors - Snap-N-Seal RCA Type Male Compression Connector



For more Information
please call

1-800-Belden1

**Description:**

Snap-N-Seal RCA Type Male Compression Connector, Compression RCA

Physical Characteristics (Connectivity)**Product Family:**

Part Number	Cable Type	Inner Pack	Sleeve Color	Outer Pack	Tool
SNS1P6RMBL	RG6	50	Blue	500	SNSUTL, CST596711, CST596
SNS1P6RMY	RG6	50	Yellow	500	SNSUTL, CST596711, CST596
SNS1P6RMW	RG6	50	White	500	SNSUTL, CST596711, CST596
SNS1P6RMR	RG6	50	Red	500	SNSUTL, CST596711, CST596
SNS1P6RMG	RG6	50	Green	500	SNSUTL, CST596711, CST596
SNS1P6RMBK	RG6	50	Black	500	SNSUTL, CST596711, CST596

Connector Type: RCA Type Male Compression

Body Components: Brass

Body Finish: NiTin

Terminal/Contact: Brass Beryllium Copper

Insulators: TPX

Mechanical Characteristics (Connectivity)

Cable Insertion Force (Max./lbs.): < 20

Cable Retention Force: 40 lbs. min. per SCTE IPS-SP-404

Temperature Rating: -40°F To +140°F

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 11/27/2008

Electrical Characteristics (Overall)

Return Loss (typical): -30 dB up to 20 MHz

Insertion Loss: -0.05 dB up to 20 MHz

RFI Shielding (typical): -120 dB up to 20 MHz

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

SNS1PRCA Drop Connectors - Snap-N-Seal RCA Type Male Compression Connector

Revision Number: 0 Revision Date: 08-26-2011

© 2012 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.