

BELDEN : Distributed by INTERSTATE WIRE CO., INC.

(800) 527-0010

**3.32: Packaging: Reels**

| OD of Wire |       | Quantity |      | Crate Reels* | Head Diameter |     | Barrel Diameter |     | Height Transverse |     |
|------------|-------|----------|------|--------------|---------------|-----|-----------------|-----|-------------------|-----|
| Inch       | mm    | 1000'    | km   |              | Inch          | mm  | Inch            | mm  | Inch              | mm  |
| .080       | 2.03  | 10.0     | 3.05 | 1748         | 15¾           | 400 | 8               | 203 | 8                 | 203 |
| .090       | 2.29  | 8.0      | 2.44 | 1748         | 15¾           | 400 | 8               | 203 | 8                 | 203 |
| .100       | 2.54  | 6.5      | 1.98 | 1748         | 15¾           | 400 | 8               | 203 | 8                 | 203 |
| .110       | 2.79  | 5.0      | 1.52 | 1748         | 15¾           | 400 | 8               | 203 | 8                 | 203 |
| .120       | 3.05  | 6.0      | 1.83 | 1747         | 15¾           | 400 | 8               | 203 | 10½               | 267 |
| .130       | 3.30  | 5.0      | 1.52 | 1747         | 15¾           | 400 | 8               | 203 | 10½               | 267 |
| .140       | 3.56  | 6.0      | 1.83 | 1746         | 17¾           | 451 | 8               | 203 | 10½               | 267 |
| .150       | 3.81  | 5.0      | 1.52 | 1746         | 17¾           | 451 | 8               | 203 | 10½               | 267 |
| .160       | 4.06  | 4.5      | 1.37 | 1746         | 17¾           | 451 | 8               | 203 | 10½               | 267 |
| .170       | 4.32  | 7.0      | 2.13 | 1744         | 22            | 559 | 10              | 254 | 14¼               | 362 |
| .180       | 4.57  | 6.0      | 1.83 | 1744         | 22            | 559 | 10              | 254 | 14¼               | 362 |
| .190       | 4.83  | 5.5      | 1.68 | 1744         | 22            | 559 | 10              | 254 | 14¼               | 362 |
| .200       | 5.08  | 5.0      | 1.52 | 1744         | 22            | 559 | 10              | 254 | 14¼               | 362 |
| .250       | 6.35  | 5.0      | 1.52 | 1743         | 26            | 660 | 10              | 254 | 14¼               | 362 |
| .300       | 7.62  | 3.5      | 1.07 | 1743         | 26            | 660 | 10              | 254 | 14¼               | 362 |
| .350       | 8.89  | 2.5      | .76  | 1743         | 26            | 660 | 10              | 254 | 14¼               | 362 |
| .400       | 10.16 | 2.0      | .61  | 1743         | 26            | 660 | 10              | 254 | 14¼               | 362 |
| .450       | 11.43 | 1.5      | .46  | 1743         | 26            | 660 | 10              | 254 | 14¼               | 362 |
| .500       | 12.70 | 1.2      | .37  | 1743         | 26            | 660 | 10              | 254 | 14¼               | 362 |
| .550       | 13.97 | 1.0      | .31  | 1743         | 26            | 660 | 10              | 254 | 14¼               | 362 |
| .600       | 15.24 | 1.2      | .37  | 1733         | 30            | 762 | 10              | 254 | 14¼               | 362 |

\*Crate Reel numbers are Belden's internal numbers. They are representative only to the extent of the dimensions shown.  
Weight of the wire may require another reel with dimensions identical to those shown