

4.2: Selection Guide

Shielded Multi-Conductor Computer Cables for RS-232 Applications

Specifications		Cable Series*			
		9925	9608	9533	9939
Conductor Size: (AWG)	28				
	24	√	√	√	
	22				√
	20				
	18				
Page No.		4.18	4.17	4.11	4.19
Insulation:	S-R PVC		√	√	√
	Polyethylene				
	Polypropylene				
	Datalene®†	√			
Shield:	Overall Foil			√	
	Drain Wire	√		√	
	Overall Foil/Braid	√	√		√
	Braid Coverage	65%	65%		65%
Drain Wire Overall:		Yes	No	Yes	No
No. of Cond. Available:	1				
	2				
	3	√	√	√	√
	4	√	√	√	√
	5	√	√	√	√
	6	√	√	√	√
	7	√	√	√	√
	8	√	√	√	√
	9	√	√	√	√
	10	√	√	√	√
	11				
	12				
	13				
	15	√	√	√	√
	17				
	18				
	19				
	20			√	
	25	√	√	√	√
	27				
	30			√	
	31				
	37	√	√		√
40			√		
50		√	√	√	
Capacitance**(pF/ft.)		12.0	30.0	30.0	35.0

*All cables are UL-listed.

**Capacitance may vary on some cables.

†Foam high density polyethylene.